



## PREMIUM DUAL EMULSION

### PRODUCT DESCRIPTION:

Soldier Premium Dual Emulsion is water based multipurpose emulsion paint specially designed for interior as well exterior surfaces providing excellent sheen and dirt pick up resistance along with long lasting performance. An ideal product for application on surfaces in dry or moderately humid climatic conditions.

### PERFORMANCE FEATURES & BENEFITS:

High Sheen	Advance color lock technology
Smooth and pleasing finish	Excellent resistance to algal and fungal growth
Excellent Aesthetic Appearance	Good Coverage & Value for Money
Excellent Dirt Pick Up Resistance	Five years warranty
Better Outdoor Durability	UV resistance
For Interior and Exterior	

### SURFACE PREPARATION:

- The surface to be painted must be free from all dust, grease, traces of paint flakes, algae and fungus etc.
- The surface previously coated with paint must be cleaned thoroughly with a stiff wire brush to remove dirt, dust, chalking or loose flakes.
- Wash thoroughly with water and allow to dry to ensure proper adhesion of the new paint system.
- In case of fungus affected area, apply a liberal coat of Nerolac Fungicidal Solution. Allow it to react for minimum of 6-8 h.
- For parapet tops and other horizontal surfaces, application of 3 coats is recommended.
- All structural cracks must be opened in V shape filled with cement and sand mixture and leakage should be stopped before actual painting.
- Freshly plastered surfaces must be allowed to cure completely for minimum of 12 weeks.

### RECOMMENDED SYSTEM FOR APPLICATION:

#### INTERIOR

Apply one coat of #Primer and allow to dry for 4-6 h.

Apply One or two coats of Soldier Cement Putty to smoothen the surface. Allow it to dry overnight.

Apply one coat of #Primer and allow to dry for 4-6 h.

Apply two coats of Soldier Dual Premium Emulsion (50% Dilution) with 4-6 h of time interval between two coats.

#### EXTERIOR

Apply one coat of #Primer and allow to dry for 4-6 h.

Apply two coats of Soldier Dual Premium Emulsion (50% Dilution) with 4-6 h. of time interval between two coats.

For horizontal surfaces and parapet tops 3rd coat is highly recommended.

For dark shades, for hiding an extra coat is recommended.

#Primer - Soldier universal Primer with 50 - 60% dilution with water or Self Priming Soldier Premium Dual Emulsion with 100% dilution with water.

## TECHNICAL DATA:



\*Actual Covering capacity may vary depending upon the method of application & condition of application, surface condition, temperature, wind velocity, application skills, surface roughness, surface porosity & shade.

## PRECAUTIONS:

- 1 Refer MSDS of Soldier Dual Premium Emulsion for safety measures & precautions.
- 2 Store in well ambient conditions, ventilated locations & away from sources of ignition & fire.
- 3 Keep away from children.
- 4 In case of eye/skin contact, wash with plenty of water.
- 5 Inhalation/Injection is dangerous. In either case, move to fresh air & consult medical practitioners.
- 6 Do not apply when ambient temperature might drop to level below 10°C within 4 h of application.
- 7 New plaster should be allowed to cure for minimum 12 weeks.
- 8 Avoid extra thinning for better results.
- 9 Do not use universal strainers. Stir paint well before application.
- 10 The container must be tightly closed when not in use. Stir well and strain before use.
- 11 Use safety equipment's like rubber or polythene gloves, safety goggles/glasses & face mask.

## POST APPLICATION INSTRUCTIONS:

For the best performance of paint, ensure proper washing and cleaning of all algae and fungal growth at regular intervals of six months.



### SAFETY FEATURES

Non-Flammable



### PACK SIZES (LITRE)

1, 4, 10 & 20



### SHADE RANGE:

As per Color Scapes Fandeck and shade card.



### NO. OF SHADES POSSIBLE

1200 - 1300